


WOOD SPEAKERS



ES-215

Order Code: TRE820409

Frequency Response : 50 Hz ... 16 kHz

Sensitivity : 97 dB

Crossover Frequency : 2.5 kHz

Dispersion (H*V) : 80° x 50°

Rated Power (RMS) : 250 W

Rated Impedance : 8 Ohm

DC Impedance : 5.6 Ohm

THD : <3%

Input connections : NI4x2 (2 x Speakon®)

Weight : 33 Kg

Dimensions : 462x440x720 mm (WxDxH)

Packing: 1 part

EAN Barcode: 5413424820409

Spare Parts :

Woofer W215,

Order code: TRE840407

Tweeter T2125

Order code: TRE840421

Recone Kit Tweeter RCT2125

Order code: TRE840438

- Two transducers two way full range
- One 15" - 38 cm woofer with big power
- One compression driver with 3" - 75 mm titanium diaphragm
- Driven by one amplifier
- 80° X 50° width direction to get more widely enlarge capability
- With computer optimize simulated design to get better frequency and phrase features.
- Suitable for full sound field enlarge, club and dancery etc publics using
- Suitable for any big sound engineering project or enlarge, returninglisten, ... And monitor us

AMPLIFIERS



UA-660

Order Code: TRE830408

Stereo 8/4/2 Ohm : 330/500/250 W x 2

Bridge 16/8/4 Ohm : 500/1000/500 W

Input Sensivity : 1 V

S/N Ratio : > 108 dB

Frequency Response : 20 Hz ... 20 kHz

THD : <0.05% @ 1 kHz 1/10 Rated Power

Slew Rate : >60 V / μs

Damping factor : >800@ 8 Ohm / 100 Hz

Input Connector: XLR/ 1/4" Socket

Input Impedance : 20KΩ (Balance)
10KΩ (Unbalance)

Output Connector : Binding posts,
NL4 Speakon®

Power Supply : 230 V AC/ 50 Hz
1.500 VA

Dimensions : 483x88x375 mm (WxDxH)

Weight : 15 Kg

Packing: 1 part

EAN Barcode: 5413424830408

- 2U rack mounting – High slew rate – Parallel operation available
- Automatic clip limiting – High damping factor
- Independent volume control for each channel, hospitable operation
- Low frequency cut point can be selected to fit different load operation
- Perfect protection, 2 Ohm impedance automatic sensing to accommodate relative parameters to keep consistency and reliability