

Description

1. Three video signal synchronous inputs available; Independent input volume control for each video channel input.
2. Manual and automatic mode for video input selection, VOD input is.
3. Classical right, left, mid and bass balance inputs channels designed.
4. RCA assistant output connectors available for right and left channel.
5. Record output connector available.
6. No polarity crossover frequency adjustable from 80Hz to 120Hz for bass channel. Independent volume control.
7. Three microphone inputs, balance controls available for treble and bass volume.
8. Sockets available for vocal effectors connection.
9. Professional anti-humming circuit design.
10. One key control DISCO equalization enhance mode.
11. Complete SMT process makes sure reliability and consistency.



KT1000

KTV Pre amplifier



SPECIFICATIONS

Power Supply

Power Supplier	AC 220V±10% 50Hz
Fuse Capacity	1A

Linn Inputs

Input Impedance/connectors	47KΩ/RCA
Left/Right Channel Output	0.775V(250mV Input)
Minimum	250mV (Output 0.775V@1KHz)
S/N Ratio	>92dB
Left/Right Assitart Channels Output	1.5V(250mV Input)
Record Output	0.775V (250mV Input)
Bass Channel Output	2.5V (Input 250mV synchronously at left and right channel)
Automatic Sensitivity Selection	12mV

Microphone Input:

Minimum Source electronotion force	10mV (Output 0.775V@1KHz)
Mid Channel Output	1.5V (10mV Input)
Dverload Source electromotive force	280mV

Dimensions and Weight

Dimensions	482 × 220 × 44 (WxDxH)
Net Weight	3kg