



acmaudio
SRP215

www.acmaudio.com





acmaudio

SRP215



Our SRP compact full range series speaker from 10", 12", 15" to double 15" display all the features expected from a product range with such a distinguished pedigree. Made from high density MDF painted in a hardwearing painted ideally suited for both mobile and fixed installation application. Perfect linear response, big dynamic and low distortion drivers with proprietary custom made voice coil are loaded and accurate crossover design make sure a clear sound available. Additionally, SRP series subwoofer will complement with SRP series full range speaker. All cabinets in SRP series are supplied with 6 strength brackets inside the cabinet and 12xM10 threaded mounting points to accommodate a number of mounting options.

Technical Specification:

Freq. Range (-10dB):	50Hz~18kHz
Freq. Response (-3dB):	60Hz~16kHz
Rec.Hipass Frequency:	30Hz
Axial Sensitivity:	100dB (1W/1m)
Max Calculated SPL:	134dB
Horizontal Coverage:	90°
Vertical Coverage:	80°
Rated System Power:	700W Continuous 2800W Peak
LF Transducer:	15"/75mm
HF Transducer:	1.4"/75mm
Crossover Frequency:	1.6kHz
Nominal Impedance:	4 ohms
Connector:	2xNL4 Speakon
Dim(HxWxD):	460mmx1145mmx516mm
Net Weight:	56Kg
Shipping Weight:	60Kg

